

SHARP®

Be Original.

PNHY431
PNHY501
PNHY551


Ultra-High Definition and Flexible Installation for 24/7 Operation



Vivid 4K UHD 24/7 operation

4 times the pixel resolution of Full-HD, showing lifelike images with incredible realism.

Full HD
LCD panel



4K Ultra-HD
LCD panel



Built-in media player provides 4K signage without a separate PC

By utilizing a commercially available USB drive, 4K still images or videos can easily be displayed without the need of a PC.


USB Memory Slot



Attach the included cover to prevent theft of a USB memory drive.

Flexible installation

PNHY series supports Landscape/Portrait/Face-up/Face-down/Tilt-forward/Tilt-backward installation.




Specifications

Model Name	PNHY431	PNHY501	PNHY551
Installation	Landscape / Portrait / Face-up / Face-down / Tilt-forward / Tilt-backward		
LCD Panel	43" class (42 1/2" diagonal) TFT LCD	50" class (49 1/2" diagonal) TFT LCD	55" class (54 5/8" diagonal) TFT LCD
Backlight	LED, full array		
Max. Resolution	3,840 x 2,160 pixels		
Max. Display Colours (approx.)	1,070 million colours		
Pixel Pitch (H x V)	0.2451 x 0.2451 mm	0.2854 x 0.2854 mm	0.315 x 0.315 mm
Max Brightness*1	500 cd/m ²		
Contrast Ratio	1,200 : 1	4,000 : 1	5,000 : 1
Viewing Angle (H/V)	178°/178° (CR ≥ 10)		
Active Screen Area (W x H)	37 1/16" x 20 13/16"	43 1/8" x 24 1/4"	47 5/8" x 26 13/16"
Response Time	8ms (grey to grey, avg.)		
Video	Analog RGB (0.7 Vp-p) [75Ω]		
Computer Input	Horizontal/vertical separation (TTL: positive/negative)		
Synchronization	VESA DDC2B		
Plug & Play	Mini D-sub 15-pin x 1, HDMI x 3		
Input Terminals*2	3.5mm mini stereo jack x 1		
Video	D-sub 9 pin x 1		
Audio	-		
Serial (RS-232C)	-		
Output Terminals*2	RCA pin (L/R) x 1		
Video	D-sub 9 pin x 1		
Audio	USB port (2.0 - compliant) x 1		
Serial (RS-232C)	10Base-T/100Base-TX		
USB Port	10W + 10W		
LAN Terminal	AC 100 - 240 V, 50/60 Hz		
Speakers Output	4 points, 400 x 400 mm pitch, M6 screw		
Power Requirement	4 points, 200 x 200 mm pitch, M6 screw		
Mounting	32°F to 104°F (0°C to 40°C)		
Environmental Conditions	20% to 80% (no condensation)		
Operating Temperature*3	-		
Operating Humidity	-		
Power Consumption (Input signal waiting state/standby mode*4)	100 W (1W / 0.5W)	110 W (1W / 0.5W)	150 W (1W / 0.5W)
Dimensions (approx.)	38 5/16" x 2 1/2" x 22 1/8"	44 7/16" x 2 1/2" x 25 9/16"	48 7/8" x 2 1/2" x 28 1/16"
Weight (approx.)	25.4 lbs	33.1 lbs	39.7 lbs


*1 Brightness depends on input mode and other picture settings. Brightness level will decrease over time. Due to the nature of the equipment, it is not possible to precisely maintain a constant level of brightness.
 *2 Use a commercially available connection cable for PC and other video connections. *3 When using the monitor lying flat on a surface (or when the monitor is tilted more than 20 degrees upward or downward from the perpendicular in relation to a level surface) the ambient temperature must be within the range of 0°C to 30°C. Temperature conditions may change when using the monitor together with optional equipment. In such cases, check the temperature conditions specified by the optional equipment. *4 No optional part is attached.

Dimensions


PNHY431



PNHY501




PNHY551



Input/Output Terminals


Bottom

(when placed horizontally)



Left side*

(when placed horizontally)
*When viewed from the front



Units: inch (mm)



SHARP
Be Original.

SHARP ELECTRONICS OF CANADA LTD.
335 Britannia Road East,
Mississauga, Ontario L4Z 1W9
1-800-567-4277 • www.sharp.ca

Printed in Canada.
VSG-VS-PNHY-E-PDF-01/2022

Sharp is a registered trademark of Sharp Corporation and/or its affiliated companies. The terms HDMI, HDMI High-Definition Multimedia Interface and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. All other brand names and product names may be trademarks or registered trademarks of their respective owners. All screen images appearing in this brochure are simulated. Design and specifications are subject to change without prior notice.