MXB427W



Desktop monochrome document systems







Sharp desktop monochrome document systems deliver leading-edge integration and powerful productivity, all in a small compact design.

A HIGHER BENCHMARK OF INNOVATION

performance

The MXB427W DESKTOP MONOCHROME DOCUMENT SYSTEM delivers crisp, high-quality output with exceptional ease-of-use. This model provides customers with an intuitive user experience and the confidence of knowing their jobs will come out right the first time, every time. Designed with robust technology and energy efficient features, the compact MXB427W delivers the productivity you need with the performance and reliability you want in your workplace or home office.

Key Features

- EASE-OF-USE 2.8" (diagonal) touchscreen display with user-friendly graphical interface provides quick access to a user guide, copy and scan settings and more.
- **PRODUCTIVITY Out-of-the-box copy**, **print**, **scan** and **fax** capabilities and **standard wireless connectivity** enables users to easily manage their workflow from PCs, smartphones and tablets.
- WORKPLACE FRIENDLY Integrates seamlessly with today's complex network environments and mobile technologies. Sharp utilizes system updates to provide feature enhancements and to ensure your machine remains compatible with current technology.

The compact **MXB427W DESKTOP MONOCHROME DOCUMENT SYSTEM** offers powerful productivity features enabling users to quickly execute workflow tasks, whether in the office, or working from home. That's the **SHARP DIFFERENCE**.



Designed to deliver convenience



A reliable document system that meets tomorrow's business needs today.

- Standard copy, print, scan and fax capability right out-of-the-box.
- Productive printing speeds of up-to 42 pages per minute.
- 50-sheet duplexing document feeder scans at speeds up-to 96 images per minute.
- Supports letter, statement and legal size paper through the standard paper drawer or bypass tray.
- Offers up-to 3 paper sources with available 900-sheet maximum paper capacity.
- 600 x 600 dpi printing delivers clear, crisp images and text page-after-page.
- 2.8" (diagonal) colour touchscreen display with user-friendly graphical interface.

10.192.20.5 10.192.20.5 Copy Copy E-mail Shortcuts Shortcuts

- Compact design easily fits into small offices or home workspaces in desktop or console configurations.
- Convenient front-facing **USB port** for **easy direct printing** of PDF files from a USB drive without having to access a PC.
- Easily copy both sides of ID, business or credit cards onto one single page.
- **Supports popular mobile technologies**, enabling users to easily print files from smartphones, tablets and even notebook computers.
- Protect your intellectual property. A wide range of security features help to keep your information safe, whether it's in a document, on the device, or over your network.
- Sharp Remote Device Manager (SRDM) allows administrators to have centralized control of the device over the network in order to simplify installation and management.*

INTUITIVE INTERFACE

STANDARD WIRELESS NETWORKING

VERSATILE DESIGN


MXB427W Specifications

Main Specifications		Main Specifications (continued)		
MXB427W	Base model includes: 50-sheet DSPF, PCL [®] 6 and PostScript [®] 3 [™] compatible printing systems, network	Device Setup	Web-based management/cloning with user/administratelevel login	
	scanning, auto duplexing, 1 x 250-sheet paper drawer,	Service/	Remote Front Panel, remote access to service logs and	
	100-sheet bypass tray. Imaging kits and starter	Functions	click counts	
	toner included.	Accessibility	Touch front panel, swipe navigation, key pad operation	
Туре	Desktop monochrome multifunction printer	Features	AT compatible print and scan drivers, AT compatible	
Display	2.8" (diagonal) colour dot matrix high-resolution touchscreen		embedded web server page, accessible user guides,	
Functions	Copy, print, network print, network scan and fax		magnification, tactile volume control, raised operator	
Originals	Sheets and bound documents		panel keys, quick copy, display brightness control,	
Max. Original			control panel key repeat adjustable.	
Size	8.5" x 14"	Environmental	International ENERGY STAR Program Ver. 3.0,	
Output Size	Min. 5.5" x 8.5", Max. 8.5" x 14"	Standards	European RoHS, Blue Angel (RAL-UZ205)	
Copy Speed	42 ppm (8.5" x 11")	Power	110-127 V AC, 50-60 HZ, 15 A receptacle	
First Copy Time	Platen Glass: 5.9	Power		
(in seconds)1	Doc Feeder: 5.9	Consumption	0.54 kW	
Magnification	25% to 400% in 1% increments	Weight	Approx. 28.2 lbs.	
Original Feed	50-sheet DSPF	Dimensions	Approx. 16.2" (w) x 14.4" (d) x 13.3" (h)	
Scan Speed	Up-to 96 ipm (Mono)/42 ipm (Colour)			
Original Sizes	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 2" x 3.5" business card	Network Printing System		
Paper Capacity	Standard: 350 sheets/Maximum: 900 sheets	PDL	Standard PCL 6 and PostScript 3 compatible	
Paper Feed	Standard: 250-sheet paper drawer and 100-sheet bypass	Resolution	600 x 600 dpi	
System ²	tray (letter/legal/statement size, envelopes through	Print Speed	42 ppm (8.5" x 11")	
	bypass only). Optional: 550-sheet paper drawer	Print Drivers	Windows Server [®] 2008, Windows Server 2008 R2,	
	(letter/legal/statement).		Windows Server 2012, Windows Server 2012 R2,	
Paper Weights	Standard and optional paper drawers: Plain and heavy		Windows Server 2016, Windows Server 2019, Window	
and Types	paper from 16-32 lb. bond. Other paper types include		Windows 8.1, Windows 10, MAC OSX® (including 10.1	
	pre-printed, recycled, pre-punched, letterhead, colour paper,		10.15), all MAC PPD, Linux® PPD	
	paper labels. Bypass tray: 16 lb. to 58 lb. bond, cover,	Mobile Printing	AirPrint, Android printing framework, Wi-Fi direct print	
	pre-printed, recycled, letterhead, colour paper, paper labels,	Print Features	Auto configuration, bar code font printing, confidential	
	card stock, envelopes.		print, custom image registration, different cover page/	
Duplexing	Standard automatic duplex copying and printing		last page/other page, document filing, duplex printing	
CPU	1 GHz multi-processor design		electronic sorting, form overlay, image rotation, image	
Interface	RJ-45 Ethernet (10/100 Base-T), USB 2.0: host, high speed		job retention, layout print, N-up printing, pamphlet sty	
	port (front), wireless LAN (IEEE 802.11 a/ac/b/g/n)		proof print, stapling, toner save mode, tray status, use	
Memory	Standard: 512 MB		authentication, watermarks, zoom print.	
Copy Resolution	Up-to 600 x 600 dpi	Direct Printing	File Types: JPEG, TIFF, GIF, BMP, PNG, PCX, PDF.	
Copy Features	Collating copies, copy shortcut, duplex copy, paper save		Methods: FTP, Web page and USB memory	
	functions (N-Up), 2 up portrait or landscape, 4 up portrait or	Resident Fonts	89 fonts (PCL), 158 fonts (PS)	
	landscape, scale (reduce/enlarge) function, maximum number	Operating	Windows Server 2008, Windows Server 2008 R2,	
	of copies 9,999, long edge binding, short edge binding.	Systems and	Windows Server 2012, Windows Server 2012 R2,	
Account Control	Supports user authentication via user-number	Environments	Windows Server 2016, Windows Server 2019, Window	
Output Tray	Centre Exit Tray (Main): 150 sheets plain paper/		Windows 8.1, Windows 10, Citrix [®] , Linux	
Capacity	10 envelopes	Printing	LPD, Raw TCP (port 9100), enhanced IP (port 9400),	
Cloud Supported	Google Drive, OneDrive for Business, SharePoint Online,	Protocols	FTP, TFTP, IPP	
Services	Dropbox and Box.			
Network	TCP/IP (IPv4, IPv6, TCP X, UDP X, IPSEC w/ IPv4 X, IPSEC	Network Scanning System		
Protocols	w/ IPv6 X, ICMP X, IGMP X, 802.1x)	Scan Modes	Standard: colour, monochrome and greyscale	
	Includes IP address filtering, protocol filtering, port control,	Max.		
Network and	includes in address intering, protocor intering, port control,			
Data Security	TLS Encryption, Kerberos	Original Size	8.5" x 14"	

Main Specificati					
Device Setup	Web-based management/cloning with user/administrator level login				
Service/	Remote Front Panel, remote access to service logs and				
Functions	click counts				
Accessibility	Touch front panel, swipe navigation, key pad operation,				
Features	AT compatible print and scan drivers, AT compatible				
1 outur oo	embedded web server page, accessible user guides,				
	magnification, tactile volume control, raised operator				
	panel keys, quick copy, display brightness control,				
	control panel key repeat adjustable.				
Environmental	International ENERGY STAR Program Ver. 3.0,				
Standards	European RoHS, Blue Angel (RAL-UZ205)				
Power	110-127 V AC, 50-60 HZ, 15 A receptacle				
Power	110 127 V A0, 50 00 112, 15 A 1000ptable				
Consumption	0.54 kW				
Weight	Approx. 28.2 lbs.				
Dimensions	Approx. 16.2" (w) x 14.4" (d) x 13.3" (h)				
Dimensions	Applox. 10.2 (w) x 14.4 (d) x 10.0 (l)				
Network Printing					
PDL	Standard PCL 6 and PostScript 3 compatible				
Resolution	600 x 600 dpi				
Print Speed	42 ppm (8.5" x 11")				
Print Drivers	Windows Server® 2008, Windows Server 2008 R2,				
	Windows Server 2012, Windows Server 2012 R2,				
	Windows Server 2016, Windows Server 2019, Windows 7,				
	Windows 8.1, Windows 10, MAC OSX® (including 10.10 to				
	10.15), all MAC PPD, Linux [®] PPD				
Mobile Printing	AirPrint, Android printing framework, Wi-Fi direct print				
Print Features	Auto configuration, bar code font printing, confidential				
	print, custom image registration, different cover page/				
	last page/other page, document filing, duplex printing,				
	electronic sorting, form overlay, image rotation, image type,				
	job retention, layout print, N-up printing, pamphlet style,				
	proof print, stapling, toner save mode, tray status, user				
	authentication, watermarks, zoom print.				
Direct Printing	File Types: JPEG, TIFF, GIF, BMP, PNG, PCX, PDF.				
	Methods: FTP, Web page and USB memory				
Resident Fonts	89 fonts (PCL), 158 fonts (PS)				
Operating	Windows Server 2008, Windows Server 2008 R2,				
Systems and	Windows Server 2012, Windows Server 2012 R2,				
Environments					
	Windows 8.1, Windows 10, Citrix®, Linux				
Printing	LPD, Raw TCP (port 9100), enhanced IP (port 9400),				
Protocols	FTP, TFTP, IPP				
Network Scanni	ng System				
Scan Modes	Standard: colour, monochrome and greyscale				
Max					

Can send bind copy of transmissions and receptions to an administrator email address, FTP or SMB location. Up-to 14* 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Fax Release, Out-of-Paper Memory Reception, Auto Redial, Auto Exposure, Group Dialing, Duplex Reception, Fax Forwarding, Colour Page and Colour Fax. Hent 550-sheet Paper Feed Unit Black Toner Cartridge				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Fax Release, Out-of-Paper Memory Reception, Auto Redial, Auto Exposure, Group Dialing, Duplex Reception, Fax Forwarding, Colour Page and Colour Fax.				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Fax Release, Out-of-Paper Memory Reception, Auto Redial, Auto Exposure, Group Dialing, Duplex Reception, Fax Forwarding, Colour Page and Colour Fax.				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Arta Release, Out-of-Paper Memory Reception, Auto Redial, Auto Exposure, Group Dialing, Duplex Reception, Fax Forwarding,				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Arta Release, Out-of-Paper Memory Reception, Auto Redial, Auto Exposure, Group Dialing, Duplex Reception, Fax Forwarding,				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Fax Release, Out-of-Paper Memory Reception, Auto Redial, Auto Exposure,				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing, Anti-junk Fax Reception, Fax Release, Out-of-Paper				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax, Quick On-line Transmission, Inbound Fax Routing,				
administrator email address, FTP or SMB location. Up-to 14" 6 MB Transaction Reports, Activity Reports, PC Fax,				
administrator email address, FTP or SMB location. Up-to 14" 6 MB				
administrator email address, FTP or SMB location. Up-to 14"				
administrator email address, FTP or SMB location.				
can send blind copy of transmissions and receptions to an				
Identification (TTI), also Document Administration function				
To email address, FTP or SMB using Transmit Terminal				
Up-to 400 groups				
ing Up-to 400 destinations (combined) aling Up-to 400 groups				
Approx. 3 seconds per page in Super G3 mode				
200 x 200 dpi (fine), 200 x 100 (standard)				
600 x 600 dpi (ultra-fine), 300 x 300 dpi (super-fine),				
Sheet fed or manual feed from platen glass				
JBIG, JPEG, MMR, MR, MH				
Speed Maximum 33.6 KBPS with auto fallback sion JBIG, JPEG, MMR, MR, MH				
Super G3, G3				
Analog PABX (RJ-11)				
on Public Switched Telephone Network (PSTN) or				
nile Function				
Optional third party applications				
POP3, LDAP, S/MIME				
HTTP/HTTPS, FTP/FTPS, SMTP/SMTP/SMTP-SSL/ESMTP,				
Email, Desktop, FTP, Folder (SMB), USB, Super G3 fax				
JPEG, PDF, PDF/A-1a/1b, XPS, TIFF				
on Colour/Greyscale: JPEG (high, middle, low)				
age Colour Scanning: Uncompressed, G3 (MH), G4 (MR/MMR)				

Network Scanning System (continued)



² Some features require optional equipment. See your local dealer.

Black Imaging Kit

MXB42DU







Design and specifications subject to change without notice. Sharp, Sharp OSA, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Microsoft, Office 365, Windows Windows Server, Excel, PowerPoint, OneDrive, and SharePoint are trademarks or registered trademarks of Microsoft Corporation. Android, Chrome, Gmail, Google Drive and Chromebook are trademarks or registered trademarks of Google LLC. Adobe, the Adobe logo, PostScript, and PostScript 3 are either registered trademarks or trademarks of Adobe in the United States and/or other countries. All other trademarks are the property of their respective owners. ©2021 Sharp Electronics of Canada Ltd.



335 Britannia Road East Mississauga, ON L4Z 1W9 www.sharp.ca