

Unique Features

Variable audio-out enables the remote control to be used to adjust the volume of self-powered external speakers that are connected to the projector. In stand-by mode, the audio-out stays active, allowing the last input used to pass to the self-powered external speakers.

Advanced AccuBlend™ ensures detailed images when non-native resolution sources are connected to the projector

64-step image magnification with location control

Built-in HTTP page for control and monitoring over a LAN network. Email notification of error messages or lamp end-of-life can be sent to remote locations.

Warranty

Registered owners receive a five (5) years or 20,000 hours (whichever comes first) parts and labour warranty.

In the Box


Remote control, batteries, power cord, cable cover, user's manual on CD-ROM, quick start guide, product registration card.

Accessories

RMT-PJ40 Replacement Remote Control
Optional Lenses NP53ZL, NP54ZL, NP55ZL
IPJ2000CM Ceiling Mount
AEC0305 Adjustable Extension Column, 3' - 5'

Ordering Model Numbers

NP-PA1505UL-B **NP-PA1705UL-B**
NP-PA1505UL-W **NP-PA1705UL-W**



		NP-PA1505UL	NP-PA1705UL	
Light Output (lumens)	Centre	15,000	17,000	
	Normal	14,000	16,000	
	ECO Mode OFF	13,500	15,300	
Resolution	Native	WUXGA 1920 x 1200		
	Maximum	4K 4096 x 2160		
Contrast Ratio (up-to)		3,000,000:1 (with Dynamic Contrast)		
Laser Life (up-to)		20,000 hours		
Screen Size (diagonal)		1.52 to 12.7m, NP53ZL, NP54ZL, NP55ZL		
Throw Ratio	NP53ZL	0.86 - 1.25:1		
	NP54ZL	1.24 - 2.01:1		
	NP55ZL	1.98 - 3.95:1		
Projection Distance		3.58 to 141 ft. / 1.09 to 43m		
Projection Angle		5.8 to 18.1° tele / 11.4 to 25.8° wide		
Lens*	Motorized			
	Zoom	NP53ZL	1.45x	
		NP54ZL	1.62x	
		NP55ZL	1.99x	
	Motorized			
	Focus	NP53ZL	Motorized zoom / focus, F=1.8 to 2.24, f= 19.0 - 27.6mm, 3.7 lbs. / 5.3 kg	
		NP54ZL	Motorized zoom / focus, F=1.8 to 2.24, f= 27.7 - 44.9mm, 3.7 lbs. / 4.5 kg	
		NP55ZL	Motorized zoom / focus, F=1.84 to 2.58, f= 43.8 - 87.2mm, 3.7 lbs. / 5.4 kg	
Shift		+/- 25% horizontal, +/- 65% vertical		
Shutter		Laser Shutter		
Keystone Correction		+/- 40° horizontal, +/- 30° vertical		
Synchronization Range	Horizontal	24-153kHz		
	Vertical	50-120Hz		
Supported Video Standards		NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM		
SD/HD Video Signal Compatibility		480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K		
PC Signal Compatibility		VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, Quad HD		
Macintosh Compatibility		Yes		
Input Terminals	RGB1 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)		
	RGB2 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)		
	RGB3 (digital)	HDBaseT w/HDCP (V1.4/2.2)		
	RGB4 (digital)	3G SDI (SMPTE ST 424M / SMPTE 292M)		
Output Terminals	Monitor Out	HDBaseT Repeater		
	Audio Out	Stereo Mini Jack		
External Control		RS-232, IR, Wired Remote, HDBaseT, DDC/Ci, RJ-45, USB (USB 2.0)		
Sync Compatibility		Separate Sync / Composite Sync / Sync on G		
Power Requirements		100-240V AC, 50/60 Hz		
Input Current		11.6A - 5.1A	12.8A - 5.6A	
Power Consumption	(Normal/Silent Mode/ Network Standby/ Standby)	960W / 855W / 0.4W / 0.15W	1035W / 855W / 0.4W / 0.15W	
Product Dimensions (WxDxH)		23.6 x 19.3 x 9.4 in. / 599 x 490 x 238 mm		
Net Weight		63.7 lbs. / 28.9 kg		
Shipping Dimensions (WxDxH)		29.1 x 24.8 x 15.0 in. / 739 x 629 x 382 mm		
Gross Weight		71.9 lbs. / 32.6 kg		
Fan Noise		38 dB normal / 35 dB silent mode	43 dB normal / 37 dB silent mode	
Regulations	USA	USA UL60950-1: 2 nd edition, FCC Part 15 Subpart B (ANSI C63.4.2014)		
	Canada	CAN/CSA C22.2 No.62368-1-18, 3 rd Edition, ICES-003 Issue 7 (ANSI C63.4-2014)		
Operating	Temperature	32-113°F / 0-45°C		
	Humidity	20% - 80% (non-condensing)		
Storage	Temperature	14-122°F / -10 50°C		
	Humidity	20% - 80% (non-condensing)		
Ordering Model Number		NP-PA1505UL-B, NP-PA1505UL-W	NP-PA1705UL-B, NP-PA1705UL-W	

* Lens does not ship with the projector. Additional accessories are available, including screens, carts, mount accessories and replacement cables. Visit www.sharp.ca for details.



SHARP ELECTRONICS OF CANADA LTD.
 335 Britannia Road East, Ste. 101
 Mississauga, Ontario L4Z 1W9
 1-800-567-4277 • www.sharp.ca

Sharp is a registered trademark of Sharp Corporation. HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. HDBase™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

Printed in Canada.
 VSG-VS-PA-E-PDF-09/2023